Cypress Soaring PW-5 Pre-Flight Checklist

Rev. 2/10/19

Remove gust locks & tiedowns												
Inspect forward fuselage												
Pitot & static ports clear												
Check weight limits												
INSTALL BATTERY-- (reqd equipment)												
Seat back secured												
Airworthiness, Registration Certif.												
Altimeter set												
Airspeed indicator- check												
Belts- check condition, latches												
Tow release-- condition												
CONTROLS-- free & operative												
Trim set-- Position 5=Heavy, Position 2=Light												
Wing bolts-- latched												
Airbrakes-- check operation												
Wheel brake operative												
Canopy locks operative												
Canopy emergency jettison pin-- installed												
Bilge clean												
Landing gear (Nose =29 psi; Main =36 psi)												
Left wing conformity												
Left aileron--deflection, play, friction												
Left wing airbrakes												
Aileron & airbrake linkages-Locked												
Fuselage access cover secure												
Left fuselage & bottom conformity												
Vertical stabilizer surfaces												
Total energy probe – installed & secure												
Rudder hinges & cables- free and operative.												
Horizontal stabilizer pin - locked												
Elevator-- check deflection, play, friction												
Tailwheel-- operational												
Right fuselage conformity												
Right wing airbrakes												
Right wing conformity												
Right aileron- deflection, play, friction												
Retract airbrakes and lock												
Radio & battery operative												
Adjust rudder pedals												
POSITIVE CONTROL CHECK												
Parachute required!												
WASH AIRCRAFT												
	Date											
PW-5 Pre-Flight Checklist	Name											