

# Cypress Soaring PW-5 N982PD - Pre Flight Checklist. Rev 02/04/22

Remove gust locks & tiedowns																	
Inspect forward fuselage																	
Pitot & static ports clear																	
Check weight limits																	
INSTALL BATTERY-- (reqd equipment)																	
Seat back secured																	
Airworthiness, Registration Certif.																	
Altimeter set																	
Airspeed indicator- check																	
RADIO - Check send and receive																	
Belts- check condition, latches																	
Tow release-- condition																	
CONTROLS-- free & operative																	
Trim set-- Position 5=Heavy, Position 2=Light																	
Wing bolts-- latched																	
Airbrakes-- check operation																	
Wheel brake operative																	
Canopy locks operative																	
Canopy emergency jettison pin-- installed																	
Bilge clean																	
Landing gear (Nose =29 psi; Main =36 psi)																	
Left wing conformity																	
Left aileron--deflection, play, friction																	
Left wing airbrakes																	
Aileron & airbrake linkages-Locked																	
Fuselage access cover secure																	
Left fuselage & bottom conformity																	
Vertical stabilizer surfaces																	
Total energy probe – installed & secure																	
Rudder hinges & cables- free and operative.																	
Horizontal stabilizer pin - locked																	
Elevator-- check deflection, play, friction																	
Tailwheel-- operational																	
Right fuselage conformity																	
Right wing airbrakes																	
Right wing conformity																	
Right aileron- deflection, play, friction																	
Retract airbrakes and lock																	
Radio & battery operative																	
Adjust rudder pedals																	
Positive Control Check																	
<b>Parachute required!</b>																	
WASH AIRCRAFT																	
	NAME																
	DATE																